




**Artikelnummer/Itemnumber: 476FU**

**Tarifnummer Export: 73269098 | Frachtkategorie: A**

Absperrpfosten, Stahlrohr  $\varnothing$  76 x 2,6 mm, umlegbar, mit Bodenplatte 100 x 150 mm, feuerverzinkt, ohne Öse

Barrier posts, steel tube  $\varnothing$  76 x 2,6 mm, foldable, to be fixed by plugs with base plate 100 x 150 mm, hot-dip galvanized, without eyelet



## Artikelbeschreibung:

Absperrpfosten, Stahlrohr  $\varnothing$  76 x 2,6 mm, mit aufgeschweißter Stahlkappe, 900 mm Überflur, umlegbar, mit Dreikantverschluss nach DIN 3223, selbsteinrastende Verriegelung, für Dübelbefestigung, mit Bodenplatte 100 x 150 mm, feuerverzinkt, ohne Öse

## item description:

Barrier post, steel tube  $\varnothing$  76 x 2.6 mm, with welded steel cap, 900 mm above ground, foldable, with triangular locking mechanism acc. with DIN 3223, self-engaging lock, to be fixed by plugs, with base plate 100 x 150 mm, hot-dip galvanized, without eyelet

## Verwendungszweck:

Zum Sperren, Sichern und Schützen von Bereichen.

## designated purpose:

For stopping, and securing or saving of areas.

## Technische Daten:

Gewicht: 7,00 kg/St  
Material:  
S235 JR

## technical specifications:

weight: 7,00 kg/pc  
material:  
S235 JR

Oberfläche:  
Feuerverzinkung nach DIN ISO 1461

surface:  
hot dipped galvanized acc. to DIN ISO 1461

\*Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

\*All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.